

# 4730 Mechanics 3

<p><b>1 i</b></p>	<p>Horiz. comp. of vel. after impact is <math>4\text{ms}^{-1}</math>                  Vert. comp. of vel. after impact is <math>\sqrt{5^2 - 4^2} = 3\text{ms}^{-1}</math>                  Coefficient of restitution is 0.5</p>	<p>B1                  B1                  B1                  [3]</p>	<p>May be implied                  AG                  From <math>e = 3/6</math></p>
<p><b>ii</b></p>	<p>Direction is vertically upwards                  Change of velocity is <math>3 - (-6)</math>                  Impulse has magnitude 2.7Ns</p>	<p>B1                  M1                  A1                  [3]</p>	<p>From <math>m(\Delta v) = 0.3 \times 9</math></p>
<p><b>2 i</b></p>	<p>Horizontal component is 14N  <math>80 \times 1.5 = 14 \times 1.5 + 3Y</math> or  <math>3(80 - Y) = 80 \times 1.5 + 14 \times 1.5</math> or  <math>1.5(80 - Y) = 14 \times 0.75 + 14 \times 0.75 + 1.5Y</math>                  Vertical component is 33N upwards</p>	<p>B1                  M1                  A1                  A1                  [4]</p>	<p>For taking moments for <math>AB</math> about <math>A</math> or <math>B</math> or the midpoint of <math>AB</math>                  AG</p>
<p><b>ii</b></p>	<p>Horizontal component at <math>C</math> is 14N                  [Vertical component at <math>C</math> is <math>(\pm)\sqrt{50^2 - 14^2}</math>]  <math>[W = (\pm)48 - 33]</math>                  Weight is 15N</p>	<p>B1                  M1                  DM1                  A1                  [4]</p>	<p>May be implied for using <math>R^2 = H^2 + V^2</math>                  For resolving forces at <math>C</math> vertically</p>
<p><b>3 i</b></p>	<p><math>4 \times 3 \cos 60^\circ - 2 \times 3 \cos 60^\circ = 2b</math>  <math>b = 1.5</math>  <b>j</b> component of vel. of <math>B = (-)3 \sin 60^\circ</math>  <math>[v^2 = b^2 + (-3 \sin 60^\circ)^2]</math>                  Speed (<math>3\text{ms}^{-1}</math>) is unchanged                  [Angle with l.o.c. = <math>\tan^{-1}(3 \sin 60^\circ / 1.5)</math>]                  Angle is <math>60^\circ</math>.</p>	<p>M1                  A1                  A1                  B1ft                  M1                  A1ft                  M1                  A1ft                  [8]</p>	<p>For using the p.c.mmtm parallel to l.o.c.                  ft consistent sin/cos mix                  For using <math>v^2 = b^2 + v_y^2</math>                  AG ft - allow same answer following consistent sin/cos mix.                  For using angle = <math>\tan^{-1}(\pm v_y/v_x)</math>                  ft consistent sin/cos mix</p>
<p><b>ii</b></p>	<p><math>[e(3 \cos 60^\circ + 3 \cos 60^\circ) = 1.5]</math>                  Coefficient is 0.5</p>	<p>M1                  A1ft                  [2]</p>	<p>For using NEL                  ft - allow same answer following consistent sin/cos mix throughout.</p>

<p><b>4 i</b></p>	$F - 0.25v^2 = 120v(dv/dx)$ $F = 8000/v$ $[32000 - v^3 = 480v^2(dv/dx)]$ $\frac{480v^2}{v^3 - 32000} \frac{dv}{dx} = -1$	<p>M1 A1 B1  M1 A1 [5]</p>	<p>For using Newton's second law with <math>a = v(dv/dx)</math></p> <p>For substituting for <math>F</math> and multiplying throughout by <math>4v</math> (or equivalent)</p> <p>AG</p>
<p><b>ii</b></p>	$\int \frac{480v^2}{v^3 - 32000} dv = -\int dx$ $160 \ln(v^3 - 32000) = -x \quad (+A)$ $160 \ln(v^3 - 32000) = -x + 160 \ln 32000$ <p>or</p> $160 \ln(v^3 - 32000) - 160 \ln 32000 = -500$ $(v^3 - 32000)/32000 = e^{-x/160}$ <p>Speed of <math>m/c</math> is <math>32.2ms^{-1}</math></p>	<p>M1 A1  M1 A1ft  B1ft B1 [6]</p>	<p>For separating variables and integrating</p> <p>For using <math>v(0) = 40</math> or <math>[160 \ln(v^3 - 32000)]^v_{40} = [-x]^{500}_0</math></p> <p>ft where factor 160 is incorrect but +ve,</p> <p>Implied by <math>(v^3 - 32000)/32000 = e^{-3.125}</math> (or = 0.0439 ..). ft where factor 160 is incorrect but +ve, or for an incorrect non-zero value of <math>A</math></p>
<p><b>5 i</b></p>	$x_{\max} = \sqrt{1.5^2 + 2^2} - 1.5 (= 1)$ $[T_{\max} = 18 \times 1/1.5]$ <p>Maximum tension is 12N</p>	<p>B1 M1 A1 [3]</p>	<p>For using <math>T = \lambda x/L</math></p>
<p><b>(a)</b></p> <p>Gain in EE = <math>2[18(1^2 - 0.2^2)]/(2 \times 1.5)</math> (11.52)</p> <p>Loss in GPE = <math>2.8mg</math> (27.44m)</p> <p><b>ii</b></p> $[2.8m \times 9.8 = 11.52]$ $m = 0.42$ <p><b>(b)</b></p> $\frac{1}{2} mv^2 = mg(0.8) + 2 \times 18 \times 0.2^2 / (2 \times 1.5)$ or $\frac{1}{2} mv^2 = 2 \times 18 \times 1^2 / (2 \times 1.5) - mg(2)$ <p>Speed at <math>M</math> is <math>4.24ms^{-1}</math></p>	<p>M1  A1  B1   M1 A1 [5]  M1  A1ft A1ft [3]</p>	<p>For using <math>EE = \lambda x^2/2L</math></p> <p>May be scored with correct EE terms in expressions for total energy on release and total energy at lowest point</p> <p>May be scored with correct GPE terms in expressions for total energy on release and total energy at lowest point</p> <p>For using the p.c.energy</p> <p>AG</p> <p>For using the p.c.energy KE, PE &amp; EE must all be represented</p> <p>ft only when just one string is considered throughout in evaluating EE</p> <p>ft only for answer 4.10 following consideration of only one string</p>	

<p><b>6</b> <b>i</b></p>	<p><math>[-mg \sin \theta = m L(d^2 \theta / dt^2)]</math> <math>d^2 \theta / dt^2 = -(g/L)\sin \theta</math></p>	<p>M1 A1 [2]</p>	<p>For using Newton's second law tangentially with <math>a = Ld^2 \theta / dt^2</math> AG</p>
<p><b>ii</b></p>	<p><math>[d^2 \theta / dt^2 = -(g/L) \theta]</math> <math>d^2 \theta / dt^2 = -(g/L) \theta \rightarrow</math> motion is SH</p>	<p>M1 A1 [2]</p>	<p>For using <math>\sin \theta \approx \theta</math> because <math>\theta</math> is small (<math>\theta_{\max} = 0.05</math>) AG</p>
<p><b>iii</b></p>	<p><math>[4\pi/7 = 2\pi/\sqrt{9.8/L}]</math> <math>L = 0.8</math></p>	<p>M1 A1 [2]</p>	<p>For using <math>T = 2\pi/n</math> where <math>-n^2</math> is coefficient of <math>\theta</math></p>
<p><b>iv</b></p>	<p><math>[\theta = 0.05\cos 3.5 \times 0.7]</math> <math>\theta = -0.0385</math></p> <p><math>t = 1.10</math> (accept 1.1 or 1.09)</p>	<p>M1 A1ft  M1  A1ft [4]</p>	<p>For using <math>\theta = \theta_0 \cos nt</math> { <math>\theta = \theta_0 \sin nt</math> not accepted unless the <math>t</math> is reconciled with the <math>t</math> as defined in the question } ft incorrect <math>L</math> { <math>\theta = 0.05\cos[4.9/(5L)^{1/2}]</math> } For attempting to find <math>3.5t</math> (<math>\pi &lt; 3.5t &lt; 1.5\pi</math>) for which <math>0.05\cos 3.5t =</math> answer found for <math>\theta</math> or for using <math>3.5(t_1 + t_2) = 2\pi</math> ft incorrect <math>L</math> { <math>t = [2\pi(5L)^{1/2}]/7 - 0.7</math> }</p>
<p><b>v</b></p>	<p><math>\dot{\theta}^2 = 3.5^2(0.05^2 - (-0.0385)^2)</math> or <math>\dot{\theta} = -3.5 \times 0.05 \sin(3.5 \times 0.7)</math> (<math>\dot{\theta} = -0.1116..</math>) Speed is <math>0.0893\text{ms}^{-1}</math></p> <p>(Accept answers correct to 2 s.f.)</p>	<p>M1  A1ft A1ft [3]</p>	<p>For using <math>\dot{\theta}^2 = n^2(\theta_0^2 - \theta^2)</math> or <math>\dot{\theta} = -n \theta_0 \sin nt</math> { also allow <math>\dot{\theta} = n \theta_0 \cos nt</math> if <math>\theta = \theta_0 \sin nt</math> has been used previously } ft incorrect <math>\theta</math> with or without 3.5 represented by <math>(g/L)^{1/2}</math> using incorrect <math>L</math> in (iii) or for <math>\dot{\theta} = 3.5 \times 0.05 \cos(3.5 \times 0.7)</math> following previous use of <math>\theta = \theta_0 \sin nt</math> ft incorrect <math>L</math> (<math>L \times 0.089287/0.8</math> with <math>n = 3.5</math> used or from <math> 0.35 \sin\{4.9/[5L]^{1/2}\}/[5L]^{1/2} </math>)</p> <p><b>SR</b> for candidates who use <math>\dot{\theta}</math> as <math>v</math>. (Max 1/3) For <math>v = \pm 0.112</math> <span style="float: right;">B1</span></p>

7 i	Gain in PE = $mga(1 - \cos \theta)$ $[\frac{1}{2} mu^2 - \frac{1}{2} mv^2 = mga(1 - \cos \theta) ]$	B1 M1	For using KE loss = PE gain
	$v^2 = u^2 - 2ga(1 - \cos \theta)$ $[R - mg \cos \theta = m(\text{accel.})]$ $R = mv^2/a + mg \cos \theta$ $[R = m\{ u^2 - 2ga(1 - \cos \theta)\}/a + mg \cos \theta]$ $R = mu^2/a + mg(3\cos \theta - 2)$	A1  M1 A1 M1 A1 [7]	For using Newton's second law radially  For substituting for $v^2$ AG
ii	$[0 = mu^2/a - 5mg]$ $u^2 = 5ag$  $[v^2 = 5ag - 4ag]$ Least value of $v^2$ is $ag$	M1 A1  M1 A1 [4]	For substituting $R = 0$ and $\theta = 180^\circ$  For substituting for $u^2 (= 5ag)$ and $\theta = 180^\circ$ in $v^2$ (expression found in (i)) { but M0 if $v = 0$ has been used to find $u^2$ } AG
iii	$[0 = u^2 - 2ga(1 - \frac{\sqrt{3}}{2})]$ $u^2 = ag(2 - \sqrt{3})$	M1  A1 [2]	For substituting $v^2 = 0$ and $\theta = \pi/6$ in $v^2$ (expression found in (i))  Accept $u^2 = 2ag(1 - \cos\pi/6)$